Vacuum Filtration System



Features

▶ No air pollution, maintenance free Rocker series pumps are piston-driven, no need of lubricant, regular oil changes and maintenance; with no oil pollution.

► The patented spin-lock design LF 30 filter holder can be connected with waste bottle by patented spin-lock connection (M381450) giving a fast and stable installation without clamp.

Drain out directly MF 31 can drain the filtrate away directly without disassembly.

► The patented magnetic design MF 31 strong magnetic seal (I551337) allows one-handed operation, prevents possible twisting and tearing of the membrane.

► International certification CE certification CSA certification (Rocker 300) IP30 protection (Rocker 300) RoHS certification (Rocker 300)

► Two-Year Warranty (Rocker 300)

Applications

- Suspended solid test
- ► Vacuum filtration

Ordering Information

167305-11(22)

Rocker 300 - LF 30, Vacuum Filtration System, complete set includes :

- * Rocker 300, Vacuum Pump
- * LF 30, Filtration Set
- * Silicone Tube (1m)

167311-11(22)

Rocker 300 - MF 31, Vacuum Filtration System, complete set includes :

- * Rocker 300, Vacuum Pump
- * MF 31, Filtration Set
- * Silicone Tube (1m)





Specification

Model	Rocker 300 - LF 30		Rocker 300 - MF 31	
Voltage / Freq.	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz
Max. vacuum	105 mbar			
Max. flow rate	23 L/min	20 L/min	23 L/min	20 L/min
Vacuum regulator	Yes			
Overflow protection	Yes			
Hose barb	ID8			
Model	LF 30		MF 31	
Funnel	300 ml		300 ml	
Receiver flask	1200 ml		1000 ml	
Filter diameter	47 mm		47 mm	
Overflow protection	Yes		-	
Drain device	-		Yes	

